



White Cold Weather Heavy Duty Hybrid PVC Food & Beverage Hose

Improved Design Stays Flexible in the Cold - Won't Crush easily in the Heat!

Drags easily-More durable-Clear FDA food grade tube-Better flexibility! Impressive!







Item	ID	OD Bend	WP	WP	Burst	Burst	Weight	Weight
<u>Number</u>	<u>(Inch)</u>	<u>(Inch)</u> Radius	<u>(PSI)</u>	<u>(Bar)</u>	<u>(PSI)</u>	<u>(Bar)</u>	(lbs/ft)	<u>(Kg/M)</u>
WCWHD-3/4-FG	3/4"	2.8	110	7	350	25	0.38	0.56
WCWHD-1-FG	1"	3.0	110	7.7	350	25	0.50	0.75
WCWHD-1.25-FG	1-1/4"	4.0	100	7.0	310	22	0.62	0.92
<u>WCWHD-1.5-FG</u>	1-1/2"	4.0	100	7.0	310	22	0.85	1.27
WCWHD-2-FG	2"	5.5	85	6.0	267	19	1.10	1.64
<u>WCWHD-2.5-FG</u>	2-1/2"	7.0	80	5.6	252	18	1.60	2.38
WCWHD-3-FG	3"	8.0	60	4.2	192	14	1.80	2.68
WCWHD-4-FG	4"	12.0	55	3.9	170	12	2.90	4.32
WCWHD-5-FG	5"	20.0	50	3.5	158	11	4.65	6.93
WCWHD-6-FG	6"	23.0	45	3.2	141	10	5.60	8.34
WCWHD-8-FG	8"	34.0	40	2.8	124	9	8.40	12.52
BCWHD-6-CL-FG	6"	23.0	45	3.2	141	10	5.60	8.34
BCWHD-8-CL-FG	8"	34.0	40	2.8	124	9	8.40	12.52



Cover: White/Blue Rasied Helical, that is flexible & wear resistant. Temp Static: Deg.-40F to 150F, Dynamic Deg -4F to 125F

Note! WPSI & Bend Radius are calculated at 70deg F. As Temperatures go up WPSI goes down & bend radius increases. Approx. a 10deg increase = -10% wpsi & bend radius+10%. When Sanitizing at higher Temperatures above 140F support the hose close to the ends to prevent kinking. Allow hose sufficient time to cool down before bending and using.